AUTOMATIC SHUT-OFF VALVES



90333-R 90335-R

Valve simply screws onto hose end. Available in straight and 90° models. Meets SAE, EPA and UL requirements for containment of refrigerant.

<< QUICK DISCONNECT : NO LOSS OF REFRIGERANT >>

90333-R	90° 1/4 x 1/4”
90333-UV	90° 1/4” FFL x 13 mm
90335-R	Straight 1/4 x 1/4”

MANUAL SHUT-OFF BALL VALVES



90430 90433

For custom application, Mastercool offers swivel ball valves without the hoses. This valve may be used to add shut-off valves to recycling equipment, manifold sets, flushing equipment, etc.

90430	1/4 x 1/4” Swivel Ball Valve
90433	1/4 x 5/16” Swivel Ball Valve

CONTROL VALVE



90328 90328-5/16

Ideal for use on charged systems. Eliminates refrigerant, oil or dye from spraying during connections.

90328	1/4” FFL x 1/4” MFL
90328-5/16	5/16” FFL x 5/16” MFL

CONNECTORS

MALE x MALE CONNECTORS



82734 82735 82736 82738 83734

82734	14 mm-M x 1/4” FL-M (7/16-20”) Connector
82735	14 mm-M x M10 x 1.5-M Connector
82736	14 mm-M x M12 x 1.75-M Connector
82738	14 mm-M x 3/8” FL-M Connector
83734	**NEW** 12mm-m x 1/4” FL-M R1234yf Connector
83341	O-Ring for 82733, 82734, 82735 and 82736
80234	O-Ring for 82634, 82634-M, 90364 and 90365

FEMALE x MALE CONNECTORS



82635 82733 90364 90363



82634 83633 83735 90366

82635	1/2” ACME-F x 1/4” FL (7/16-20”)-M R134a Adapter Coupler
82733	14 mm-F x 1/2” ACME-M Connector
90364	1/4” (7/16-20”)-F x M10 x 1.5-M Adapter
90363	5/16” (1/2-20 UNF)-F x 1/4” FL-M Connector
82634	1/4” FL-F (7/16-20”) x 1/2” ACME-M R134a Connector
82634-M	1/4” FL-F (7/16-20”) x 1/2” ACME-M R134a Connector without check valve
83633	**NEW** 1/2” ACME-M x 1/2” ACME-F LH Connector
83735	**NEW** 12mm-M x 14mm-F R1234yf Adapter
90366	1/4" SAE FL-F x 5/16" FL-Male